

A predictive control algorithm to optimize the operation of heat pumps in residential buildings in the context of smart grids

Philippe ANDRE and Elisabeth DAVIN,
BEMS, University of Liège, Arlon Campus Environnement

Jonathan MAUS, Master Student
University of Liège, Gembloux Agro-Biotech

Belgium




Context of the Flexipac project

- Flexipac: research project funded by the walloon region of Belgium between 2013 and 2015
- Reasons for the research:
 - Increasing share of renewable (intermittent) electricity sources
 - Need for grid development and reinforcement for balancing loads on the grid and on the market
 - Increasing use of heat pumps as a substitute to fossil fuel boilers
 - Heat Pumps have the potential to shift electricity demands by means of short term thermal storage




Objective of the Flexipac project

- Development and test of an intelligent controller for a heat pump, based upon the « Model Predictive Control » paradigm, to be applied to residential buildings




Model Predictive Control principle



Components of the Model Predictive Control

- State-space model of the system
- Disturbances forecasting
 - Weather
 - Occupancy of the house
- Optimisation algorithm



Methodology

- Development of the model
- Identification of the parameters
- Selection of the optimisation algorithm
- Experimentation:
 - In simulation
 - In laboratory building



Development of the model

■ Building modelling approaches:

□ White box (physical, knowledge)

- Detailed
- Many parameters
- Not suitable for optimization



□ Black box (statistical, representation)

- Simplified
- Reduced number of parameters
- Suitable for optimization



Development of the model


■ Grey-box approach

- Stil « simplified »
- Reasonable number of parameters
- Suitable for optimization



■ Electrical analogy is very often used for a compact representation of model


- Parameters
- States



Testing environment: laboratory house




Energy systems laboratory
on the Arlon campus



Heating system: floor heating



Modelling of the house



3 state variables; 4 inputs



Modeling of the house: equations

$$\frac{dT_m}{dt} = -\frac{(R_e + R_i)}{C_m R_e R_i} T_m + \frac{1}{C_m R_e} T_e + \frac{1}{C_m R_i} T_i$$

$$\frac{dT_i}{dt} = \frac{1}{C_i R_i} T_m - \frac{(R_i R_{pl} + R_i R_f + R_{pl} R_f)}{C_i R_i R_{pl} R_f} T_i + \frac{1}{C_i R_{pl}} T_{pl} + \frac{1}{C_i R_f} T_e + \frac{1}{C_i} Q_{in}$$

$$\frac{dT_{pl}}{dt} = \frac{1}{C_{pl} R_{pl}} T_i - \frac{(R_{pl} R_{inpl} + R_{pl} R_{grd} + R_{inpl} R_{grd})}{C_{pl} R_{pl} R_{inpl} R_{grd}} T_{pl} + \frac{1}{C_{pl} R_{inpl}} T_{inpl} + \frac{1}{C_i R_{grd}} T_{grd}$$


State-space formulation with

$$A = \begin{bmatrix} \frac{(R_e + R_i)}{C_m R_e R_i} & \frac{1}{C_m R_i} & 0 \\ \frac{1}{C_i R_i} & -\frac{(R_i R_{pl} + R_i R_f + R_{pl} R_f)}{C_i R_i R_{pl} R_f} & \frac{1}{C_i R_{pl}} \\ 0 & \frac{1}{C_{pl} R_{pl}} & -\frac{(R_{pl} R_{inpl} + R_{pl} R_{grd} + R_{inpl} R_{grd})}{C_{pl} R_{pl} R_{inpl} R_{grd}} \end{bmatrix} \quad B = \begin{bmatrix} \frac{1}{C_m R_e} & 0 & 0 & 0 \\ \frac{1}{C_i R_f} & 0 & 0 & \frac{1}{C_i} \\ 0 & \frac{1}{C_{pl} R_{inpl}} & \frac{1}{C_{pl} R_{grd}} & 0 \end{bmatrix} \quad C = \begin{bmatrix} 0 \\ 1 \\ 0 \end{bmatrix}$$



Parameters identification

- Use of a test sequence $fit = 100 \left(1 - \frac{\|y - \hat{y}\|}{\|y - moy(y)\|}\right)$
 - 5 days
 - 5 minutes sampling time



Optimisation algorithm

- Model-based Predictive Control (MPC)
- Variables:
 - Controlled variable: indoor temperature
 - Control variable: supply temperature of the floor heating system
 - Disturbances:
 - Measured:
 - « Outside » temperature
 - Internal gains
 - Non measured: none



Optimisation algorithm

- Time step: 15 minutes
- Horizons:
 - Prediction horizon: 48 hours
 - Optimization horizon: 6 hours
 - Control horizon:
 - Receding: 15 minutes (the next time step)
 - Non receding
- Algorithm: « mpc » command of MatLab®




Cost function

$$\min_{\Delta u(k|k), \dots, \Delta u(m-1+k|k), \epsilon} \left\{ \sum_{i=0}^{p-1} \sum_{j=1}^{n_s} |w_{i+1}^y (y_j(k+i+1|k) - r_j(k+i+1))|^2 + \sum_{j=1}^{n_s} |w_{i,j}^u u_j(k+i|k)|^2 + \sum_{j=1}^{n_s} |w_{i,j}^t (u_j(k+i|k) - u_{j,\text{target}}(k+i))|^2 \right\} + \rho_\epsilon \epsilon^2$$

- Includes 3 terms:
 - Setpoint deviation (comfort) + hard constraints
 - Control variations (wear of equipment)
 - Control cost, including variable electricity price (cost, reflecting load on the network)
- Each term is weighted



Weather forecasting




Connection to a weather model

Modèle Global 50km

Modèle Régional Grille 1 15km

Modèle Régional Grille 2 5km




Internal disturbances are artificially generated in the lab



Emulation of internal gains →

Scénario zone "Piece de vie"



Testing

- In laboratory building:
 - Realistic
 - Controlled and replicable
- Objective
 - To assess, on site, the behaviour of the controller
 - To measure the impact of the Demand-Side Management on the thermal comfort of the occupant




Testing conditions and limitations

- Test 1
 - Average weighting factors
 - Ideal weather forecasts
 - Receding horizon
- Test 2
 - Weighting factors:
 - First phase: energy cost priority
 - Second phase: comfort priority
 - Real weather forecasts
 - No longer receding horizon
- Test 3
 - Weighting factors: average
 - Variable setpoint
 - Real weather forecasts
 - No receding horizon
- Limitations
 - Energy cost is expressed by the supply temperature
 - Heat storage is limited (low inertia floor heating system)
 - Water storage not included in the optimisation
 - Load on the grid is supposed to be translated by the electricity price




Results: test 1




6 days; comfort is maintained; heat pump operation is imposed by a combination of factors

Results: test 2



Results: test 3



6 days; average weighting factors; variable setpoint; much more fluctuating internal gains
No longer receding horizon

Conclusions and perspectives

- Experimental testing, in conditions close to reality, demonstrate the ability of a predictive controller to optimize the heat pump operation strategy
- Next steps:
 - Inclusion of the storage in the optimisation
 - Application to real houses
 - Application to larger number of houses -> global optimisation problem
 - Integration of local renewable electricity production (prosumers)

Thank you for your attention



This research was conducted with the support of the wallon region of Belgium

